



TRUESDAIL LABORATORIES, INC.

3337 MICHELSON DRIVE, SUITE CN 750, IRVINE, CA 92612

Certified Product Listing

For:

Drinking Water System Components – Health Effects

Company:

Picote Solutions, Inc.
20810 SE 18th Place
Sammamish, WA 98075, United States

Plant Location:

SO Salt Lake, UT, United States

Standards:

NSF/ANSI 61 Section 5 - 2016

Certificate:

Issued: 03/29/2017
Expires: 12/31/2022

Material/Product:

Coatings

Contact Temperature:

23 ± 2°C

Models:

DC1000E



Product certified to NSF/ANSI 372 conforms to the requirements for “Lead Free” plumbing products as defined by California, Vermont, Maryland and Louisiana state laws and by section 1417 of the US SDWA.



Material Characteristics:

Minimum pipe diameter (inches): 4

Maximum pipe surface area/volume ratio (sq in/L): 61

Minimum tank size (gallons): 50

Maximum tank surface area/volume ratio (sq in/L): 16.8

Maximum dry film thickness per coat (mils): 125

Number of coats: 1

Is additional coating required (e.g. top coat, primer, intermediate coat)? (Y/N): No

Total cure time and temperature: 4 days @ 70°F

Shortest cure time between coats or layers: 2 hours

Final cure time: 4 days @ 70°F

Mix ratio: 2:1

Colors: White

Is this paint/coating system intended to be applied to a pipe? (Y/N): Yes

(1) Certified for use on a new pipe? (Y/N): Yes

(2) Certified for use on a pipe intended for immediate return to service? (Y/N): No

Additional comments:

Flushing or preparation instruction prior to use:

a) Flushing Time: General Flush at 15 minutes

b) Temperature of Flush: 23 ± 2 °C